




# 1D MANUAL HEIGHT GAGE (WITHOUT AIR CUSHION) **CODE DHG-C420**

**♦///S/ZE→** PLUS MADE IN EUROPE








- Set 9 reference pointsProbe can be moved quickly by hand
- Touch buttons
- LED display with backlight
- Measurement results can be sent to Excel/Word, equivalent to keyboard input



**DHG-C420** 



### **SPECIFICATION**

OI EOII IOATION		
Measuring range	0~406mm	
Accuracy (at 20°C)	8µm	
Repeatability	3µm	
Resolution	0.1mm, 0.01mm, 0.001mm (selectable)	
Data output	USB	
Measuring force	0.75N, 1N, 1.25N, 1.5N (selectable)	
Power supply	AC/DC adapter	
Working temperature	10°C~40°C	
Weight	21kg	

measure height between measuring point and datum point

maximum, minimum, TIR measurement

calculate difference between two Δ measured values

Ø measure diameter and center of shafts

calculate average value of two measured values

#### STANDARD DELIVERY

Main unit	1 pc
Ø4mm ruby ball probe	1 pc
Calibration block	1 pc
AC/DC adapter	1 pc
Software and USB cable	1 pc

## OPTIONAL ACCESSORY

OI HONAL ACCECCON		
Transmitter	7306-100	
Receiver	7306-2	
Rechargeable battery	ISHH-V-BATTERY	
Probe	ISHH-V-C2A ISHH-V-C4A ISHH-V-R4 ISHH-V-R5B ISHH-V-R10 ISHH-V-P1	

To be continued